ARTICLE CODE	DESCRIPTION
MKL-5004	Isothermal container Koala 500 - 715x850x1915mm - ventilated cooling - -18°C +10°C - top cooling

BRAND

Melform

PRODUCT DESCRIPTION

Ventilated cooling container with front door opening and 1 guide on 4 wheels
Optional PVC grid WMC-7001 available
Monobloc molded inner and outer walls in impact-resistant polyethylene
Suitable for intensive and professional daily use
Insulation core: injected high-density polyurethane free of CFCs and HCFCs
Operating temperature as isothermal container, without ventilation cooling: -30°C to +75°C
Temperature control ventilation cooling: -18°C to +10°C
Ventilated cooling is located at the top of the container
Ventilated cooling ensures faster and more even temperature distribution in the container
Wheel forks produced from galvanized steel
Type of wheels: Rubber tread on PA core, Ø 100 mm
Standard 2 fixed wheels and 2 swivel wheels, 1 swivel wheel with brake
Perfect hygiene thanks to smooth finish
Internal groove structures for better air circulation
No welds, no sharp edges thanks to rotomolded monostructure
Quick and easy to clean
Fully recyclable
Programmable digital thermostat with monitoring function during transport
Durable stainless steel locking handle with practical release button
Hinges in sturdy stainless steel
With integrated stainless steel handles for safe and smooth handling
Door with gasket can be opened up to 270°
Int. dim.: L540 x W660 x H1170 mm
Dual power supply: 12 Vdc and 230 Vac





SPECIFICATIONS

Length (mm)	715
Width (mm)	850
Height (mm)	1915
Net weight (kg)	120
Matter	• Insulated polyethylene • Polyurethane
Color	Undefined

TECHNICAL DETAILS

MOQ sales (Pc.)	1