ARTICLE CODE	DESCRIPTION
PPC-1310	Pallet Solid line - 1200x1000x160mm - closed deck - 3 skids - recycled

BRAND

Cabka











PRODUCT DESCRIPTION

Reusable pallet suitable for long-term use
Impact-resistant material - without metal reinforcements
Universal, durable and environmentally friendly solution for storage, distribution, closed loops or export, pharmaceuticals & laboratory, healthcare sector, etc.
Suitable for intensive use in high-rotation logistics, semi-hygienic environments
Temperature resistant from -20°C to +40°C, cleaning up to +65°C (max. 10 min.) and short-term surface steaming up to +100°C
Weather and UV resistant
Easy cleaning
Rounded impact zones reduce risk of damage to a minimum
Raised edges ensure optimal transport security and stability
Options: anti-slip structures, customisation, etc.
100% recyclable at end of life
Entry height short side: 119 mm
Entry height long side, between runner and deck: 95 mm
Maximum static load: 6000 kg
Maximum dynamic load: 2500 kg
Maximum racking load: 1250 kg
Packaging: 15 pallets/stack

SPECIFICATIONS

Length (mm)	1200
Width (mm)	1000
Height (mm)	160
Net weight (kg)	21.5
Matter	Recycled polypropylene
Color	Anthracite

TECHNICAL DETAILS

ETIM	EC004004
MOQ sales (Pc.)	1

ATTRIBUTES

Model	Solid line
Gs Certificate	false
Quantity Par Stack	15
Load Capacity Static (kg)	6000
Load Capacity Dynamic (kg)	2500
Type Of Surface	Closed deck
Nestable	false
Load Capacity In Rack (kg)	1250
Entry Height	Ingångshöjd kortsida: 119 mm // Ingångshöjd långsida, mellan löpplattan och däcket: 95 mm //
Quantity Skids	3