ARTICLE CODE	DESCRIPTION
MKL-1500	Isothermal container Koala 150 - 570x1045x690mm - static cooling - -25°C +10°C - rear cooling

BRAND

Melform







PRODUCT DESCRIPTION

Static refrigerated container with front door opening
Optional stainless steel guides (WMC-6221), raised stainless steel grid (WMC-7130) or standard stainless steel grid (WMC-7100) available
Monoblock moulded inner and outer walls in impact-resistant polyethylene
Suitable for intensive and professional daily use
Insulation core: injected high-density polyurethane free of CFC and HCFC
Operating temperature as isothermal container, without static cooling: -30° to +75°C
Temperature control static cooling: -25°C to +10°C
Static cooling located at the rear of the container
Perfect hygiene thanks to smooth finish
Internal groove structures for better air circulation
No welded seams, no sharp edges thanks to rotomoulded monostructure
Quick and easy to clean
Fully recyclable
Programmable digital thermostat with monitoring function during transport
Shock-resistant locking bracket in polyamide and fibreglass
Hinges in shock-resistant material
With integrated stainless steel handles for safe and easy movement
Door with seal can be opened up to 240° and removed for optimal cleaning
Pressure control valve in door for ideal pressure control
Suitable transport trolley: MKL-0006
Containers can be stacked perfectly on top of each other and secured with connector WMC-6230
Int. dim.: L430 x W650 x H520 mm
Dual power supply: 12Vdc and 230Vac

SPECIFICATIONS

Length (mm)	570
Width (mm)	1045
Height (mm)	690
Net weight (kg)	55
Matter	• Insulated polyethylene • Polyurethane
Color	Undefined

TECHNICAL DETAILS

MOQ sales (Pc.)	1